

A Mathematical and Computational Framework for the Adoption of AI-Driven Cloud Robotics Systems

Khaled Omar Al-Sheyyab¹, Hasan Al-Refai², Mohammed Salem Ahmed Amayreh³, Rizik Al-Sayyed⁴, Ghassan Samara⁵, Sawsan S. Badrakhan⁶, and Mahmoud Odeh^{7,*}

¹ Faculty of Arts and Sciences, Al-Ahliyya Amman University, Amman, Jordan

² Cybersecurity Department, Faculty of Information Technology, American University of Madaba, Madaba, Jordan

³ Department of History, Faculty of Arts, Ajloun National University, Ajloun, Jordan

⁴ King Abdullah II School of Information Technology, The University of Jordan, Amman, Jordan

⁵ Department of Computer Science, Faculty of Information Technology, Zarqa University, Amman, Jordan

⁶ Department of Humanities and Social Sciences, Faculty of Arts & Science, Al-Ahliyya Amman University, Amman, Jordan

⁷ Department of Cybersecurity, Faculty of Information Technology, Zarqa University, Amman, Jordan

Received: 15 Jan. 2026, Revised: 7 Mar. 2026, Accepted: 13 Oct. 2026

Published online: 1 Nov. 2026

Abstract: Cloud technology gave rise to the advent of AI-Driven Cloud Robotics, which is essentially the amalgamation of AI, Robotics and cloud computing. This makes it possible to configure a robotic system in such a way that multiple robotic agents can share computational resources, data, models through cloud infrastructures. These systems continue to encounter a multitude of bottlenecks, distinctly stemming from communication barriers of which the most prevalent is the increased time caused by latency in transferring information between the robotic agent and the cloud, energy expenditure caused by the robotic agent battery, the possibility of successfully completing missions, usage and cloud cost requirements. This research therefore presents a quantitative decision-making mathematical and computational model for studying and adopting the optimal use of next-generation AI-Driven Cloud Robotics systems. The goal of the research is to develop a formally scalable mathematical model an open-problem for the exceedingly vague AI-Driven Cloud Robotics domains. The Adoption Readiness Index (ARI) is defined as a bounded multivariable optimization problem that considers all of mission success probability, time delay in transferring information, energy expenditure and cost per energy load for cloud usage. The unified task and cloud, latency and energy usage representation are described in the form of a directed acyclic graph-based task modeling process. The graph-based task representation can also be used in formulating the designs for distributed cloud system control for coordinating tasks between the cloud and the edge. Rigorous simulation studies are utilized, which highlight that the new immediate obsolescence cost benefits optimization problem will advance the state of the art for the development of scalable computer-aided task planning new missions and robotic systems in the decision-making developmental phase with a high level of detail.

Keywords: AI-Driven Cloud Robotics; Applied Mathematical Modeling; Cloud-Edge Computing; Optimization Theory; Distributed Control; Intelligent Information Systems.

1 Introduction

Artificial Intelligence and Robotics are considered enabling technologies for the Fourth Industrial Revolution providing automation, intelligent decision, and autonomy. Over the last decade, advances in machine learning, particularly deep learning and reinforcement learning, have endowed robots with super human functional ability to sense complex environments, adapt to uncertainty, and interact in ways that were beyond reach [1]. Yet, the computational costs of state-of-the-art AI algorithms

made the underlying limits of the classic robotic architecture obvious. Stand-alone robotic systems are limited by onboard processing power, memory, and energy, which limits the complexity and scope of intelligence that can be reasonably integrated. Cloud and edge computing have been proposed as an injection point to unlock this limit, giving rise in the process to the cloud robotics paradigm. With respect to cloud robotics, AI-driven cloud robotics allows robots to offload big data demand computations to the cloud, share sensory data

* Corresponding author e-mail: modeh@zu.edu.jo




Fig. 1: Predictive Maintenance Framework for IoT Robotic [25]

with the cloud, and learn in a cooperative manner. Robots become networked cyber-physical agents updating dynamically with cloud resources for improved perception planning and control functions [2]. The promise includes scalable intelligence and sharing learning, cheaper hardware, and superior performance measures among others [3]. There has been little adoption of AI-Driven Cloud Robotics so far, due to specific and often raised concerns of industrial stakeholders, that none prediction of communication latency and reliability, second the transmission cost in terms of energy, third the consistency and reliability with distributed cloud control, the practice data confidentiality and privacy in the shared cloud and fifth the complete absence of quantitative tools for the assessment of the advantages of the adoption [4-7]. Among them, the issue of transmission cost has specifically been addressed in previous work and validated in real experiments [8].

2 Related Work

The recent explosion of interest in cloud robotics and increased reliance on resource constrained robots demands continued attention to these lines of research [9]. New openings include incorporating Pricing as a Service (PaaS) within cloud robotics reconciliation beneficial offloading with transaction fees in partial cloud systems and emergent job assignment in large-scale aggressive cloud networks [10].

2.1 Cloud Robotics Architectures

Initial research works on cloud robotics and automation are conducted and the significance of cloud resources for robotic perception and learning is brought to the forefront




Fig. 2: AI-Driven Cloud Robotics Workflow for the adoption of AI-cloud robotics technology

[11]. Based on this first step, other researchers propose concepts of middleware framework-integrated robotics that interoperate with cloud services for task decision and content sharing [12]. While such conceptual mockups may be implementable, they overgeneralize the cementation of the adoption context and merely present a high-level blueprint of system design.

2.2 Task Offloading and Optimization

Research on task offloading in mobile, and edge cloud computing environments has addressed the introduction of optimization-based approaches (fabula) that maximize the minimization of either time delays or energy costs associated with dynamically offloading tasks among local or remote resources [13]. Nonetheless, such models typically either implicitly assume devices of equal capacity, or do not consider the issue of control stability [14].

2.3 Distributed Control in Networked Robotics

Distributed control theory has served as the mathematical basis for coordination of multi-agent robotic systems. Consensus-based algorithms, graph Laplacian analysis, as well as cooperative control strategies have been extensively studied [15]. However, these do not explicitly or implicitly address the cloud offloading decision-making, nor have been investigated in the related literature from an economics perspective [16].

2.4 Adoption-Oriented Modeling

There is not much research done on mathematically modeling the adoption of cloud robotics. The adoption models from existing information systems research are mostly conceptual or based on qualitative observations in the field, lacking the needed accuracy for system-level assessments [17-20]. We identify this as a research gap to be addressed by developing an approach that is mathematically precise and based on practical realities.

3 Problem Formulation and Mathematical Preliminaries

Deciding to adopt AI-Driven Cloud Robotics (ACR) may be viewed as a multi-objective optimization problem under sustainability, efficacy, and trust constraints. To reach a near-optimal integration, proper weighting is assigned to the following objectives and constraints: 1. Objective 1: Maximum sustainability, efficacy, and trust: The cloud computing environment enables a continuation of physical and virtual sustainability. Free of charge access to data centers offers scalable resources and services on a pay-per-use foundation. 2. Objective 2: Maximum sustainability: By providing urgency-driven and CPU-intensive functionality centrally on-demand. This alleviates robotic hardware requirements, size, weight, and electrical power use. 3. Objective 3: Maximum efficacy: The cloud model expands the robot's computing and storage capabilities which are effective when the task requires supervision [26].

An observer can see an infrastructure of information security governance in layers that incorporates underlying areas technology, processes, organization, and people, within an overlay of governance supported by foundational auditing, policy administration, compliance, risk management, and continuous monitoring elements. The overarching architecture of the region-specific framework is oriented to international standards and best practices is expected to support effective information security risk assessment, regulatory compliance, and organizational resilience [27].

4 System Assumptions

The following assumptions are made to ensure mathematical tractability while maintaining realism:

1. Finite multi-agent system:
Let $N = \{1, 2, \dots, N\}$ denote the set of robotic agents, where:
2. Task decomposability: Each task T_k can be partitioned into a finite collection of modular subtasks, that is,

$$T_k = \{\tau_{k1}, \tau_{k2}, \dots, \tau_{kn_k}\}$$

where each sub-task τ_{kj} may be processed either locally by a robot or offloaded to the cloud.

3. Bounded communication latency: The communication delay between any robot and the cloud, or between two robots, is time-varying but bounded. Hence, for latency $L_{ij}(t)$,

$$0 \leq L_{ij}(t) \leq \bar{L}, \quad \forall i, j, \forall t$$

where $\bar{L} < \infty$ is the maximum admissible delay.

4. Finite cloud capacity: Cloud computational resources are limited. If C_{cloud} denotes the total available cloud capacity, then any admissible allocation must satisfy

$$\sum_k \sum_j r_{kj} x_{kj}^{\text{cloud}} \leq C_{\text{cloud}}$$

where r_{kj} is the resource demand of subtask τ_{kj} , and $x_{kj}^{\text{cloud}} \in \{0, 1\}$ whether the subtask is assigned to the cloud.

4.1 Mathematical Graph Theory

Let the robotic system be represented by an undirected graph $G = (V, E)$. Where V denotes the set of robots and E represents communication links.

The graph Laplacian is defined as:

$$L = D - A$$

where D is the degree matrix and A is the adjacency matrix.

The Laplacian plays a central role in analyzing consensus and stability of distributed control algorithms.

4.2 Optimization Theory

Consider a general constrained optimization problem of the form

$$\min_{x \in X} f(x)$$

$$\text{subject to } g_i(x) \leq 0, \quad i = 1, 2, \dots, m$$

where $f : X \rightarrow \mathbb{R}$ denotes the objective function and $g_i : X \rightarrow \mathbb{R}$ represent the constraint functions. It does not assume global convexity for both the objective function and the set of constraints, which is in line with the intrinsic nonlinearity and complexity of cloud robotics systems, and the resulting optimization problem in general is a non-convex one.

4.3 Mathematical Model for Adoption Readiness (System-Level Variables)

Let:

- $R = \{r_1, r_2, \dots, r_N\}$ be the set of robots,
- $T = \{t_1, t_2, \dots, t_M\}$ be the set of tasks.

For each task t_j , define:

- L_j : end-to-end latency,
- E_j : energy consumption,
- S_j : probability of successful completion,
- Cost: cloud operational cost,
- C_j : required cloud computational resources.




Fig. 3: A Mathematical Flowchart of the Artificial Bee Colony Algorithm for Optimal Task Offloading in Edge-Cloud Computing




Fig. 4: Proposed framework for AI-Driven Cloud Robotics Adoption Optimization Framework (ACROF)

4.4 Adoption Readiness Index (ARI)

We define the Adoption Readiness Index (ARI) as a scalar-valued objective function:

$$ARI = \sum_j (w_1 S_j - w_2 L_j - w_3 E_j - w_4 C_j)$$

where S_j , L_j , E_j , and C_j denote, respectively, the benefit score, latency, energy consumption, and cost associated with the j -th component or service. The coefficients $w_1, w_2, w_3, w_4 \geq 0$ are weighting parameters that encode organizational priorities and preferences.

4.5 Constraints

The optimization problem is subject to the following constraints:

1. Cloud Capacity Constraint

$$\sum_j C_j \leq C_{\max}$$

which ensures that the total allocated cloud resources do not exceed the available system capacity.

2. Latency Constraint

$$L_j \leq L_{\max}, \quad \forall j$$

which guarantees that the latency of each task remains within the acceptable real-time threshold.

3. Reliability Constraint

$$S_j \geq S_{\min}, \quad \forall j$$

which enforces a minimum acceptable level of reliability (e.g., task success probability) for all components.

5 Interpretation of the Model

The ARI provides a single quantitative metric that enables comparison between different architectural choices:

- Standalone robotics,
- Edge-only systems,
- AI-Driven Cloud Robotics.

A positive improvement in ARI under cloud integration indicates favorable adoption conditions.

6 Simulation Environment

A discrete-time simulation environment in which we can model a multi-robot system that operates in a shared workspace. We make sure to choose simulation parameters that are based on real-world industrial and service robotics scenarios.

6.1 System Parameters

Each robot executes heterogeneous tasks with varying computational and energy demands.

Parameter	Value
Number of robots N	20
Tasks per robot	5–10
Cloud latency	20–120 ms
Edge latency	5–15 ms
Cloud capacity $C_{\max}$	100 units
Simulation horizon	10,000 steps

6.2 Simulation Procedure

1. Initialize the states of the robots and the conditions of the network.
2. Distribute the tasks in the SR, ER, and ACR settings.
3. Use Algorithm 1 to offload the tasks in the ACR.
4. Control in a distributed way by using Algorithm 2.
5. Update the learning models by using Algorithm 3.
6. Store the metrics at each simulation step.
7. Repeat the above steps with several random seeds.

7 Results and Performance Analysis

The ACR setup has way lower average task latency than SR or ER. Cloud communication has some overhead but intelligent offloading makes sure stuff that needs low latency stays on the robot. In numbers:

- The set SR baseline latency to 1.0,
- ER lowers it to about 0.82,
- And on average ACR has latency of 0.65 which is 35% less than just the robot.

7.1 Energy Consumption Analysis

Energy consumption is influenced by both computation and communication. Although cloud communication incurs energy cost, offloading reduces onboard computation burden.

Simulation results show:

- SR energy consumption baseline = 1.0,
- ER = 0.91,
- ACR = 0.82.

This reflects an 18% reduction in average energy usage per task.

7.2 Task Success Rate and Reliability

Task success probability improves significantly under ACR due to access to shared models and global optimization.

$$\bar{S}_{SR} = 0.78, \quad \bar{S}_{ER} = 0.84, \quad \bar{S}_{ACR} = 0.95.$$

$$\bar{S}_{SR} = 0.78, \quad \bar{S}_{ER} = 0.84, \quad \bar{S}_{ACR} = 0.95.$$

The 22% improvement in task success validates the reliability benefits of cloud-enabled intelligence.

Algorithm 1: Task Allocation for Maximizing Adoption Readiness

Input: set of tasks $T = \{t_1, t_2, \dots, t_M\}$; for each task t_j :
 L_j = latency, E_j = energy consumption, S_j = reliability, $Cost_j$ = cost, C_j = required cloud capacity; Weights: w_1, w_2, w_3, w_4 ; Constraints: $C_{\max}, L_{thr}, S_{\min}$

Output: Allocation map A (Cloud or Edge for each task)

```

1 begin;
2 CloudTasks ← empty set;
3 EdgeTasks ← empty set;
4 UsedCapacity ← 0;

// Step 1: Compute ARI score for each task
5 foreach task  $t_j$  in  $T$  do
6    $ARI_j \leftarrow (w_1 * S_j) - (w_2 * L_j) - (w_3 * E_j) - (w_4 * Cost_j)$ ;

// Step 2: Sort tasks by ARI in descending order
7 Sort  $T$  in descending order based on  $ARI_j$ ;

// Step 3: Assign tasks
8 foreach task  $t_j$  in sorted  $T$  do
9   if ( $UsedCapacity + C_j \leq C_{\max}$ ) AND ( $L_j \leq L_{thr}$ ) AND ( $S_j \geq S_{\min}$ ) then
10    Assign  $t_j$  to Cloud;
11    Add  $t_j$  to CloudTasks;
12     $UsedCapacity \leftarrow UsedCapacity + C_j$ ;
13   else
14    Assign  $t_j$  to Edge;
15    Add  $t_j$  to EdgeTasks;

// Step 4: Output result
16  $A \leftarrow \{CloudTasks, EdgeTasks\}$ ;
17 return  $A$ ;
18 end;
```

Algorithm 2: Distributed Consensus Control

Input: $R \leftarrow$ set of robots $\{r_1, r_2, \dots, r_N\}$; $N_i \leftarrow$ set of neighbors for each robot r_i ; $x_i \leftarrow$ state of robot r_i
Output: Coordinated robot states

```

1 Begin
2 Initialize states  $x_i$  for all robots
3 Repeat until convergence:
4   foreach robot  $r_i$  do
5     Receive states  $x_j$  from all neighbors  $j \in N_i$ 
6      $u_i \leftarrow 0$ 
7     foreach neighbor  $r_j$  in  $N_i$  do
8        $u_i \leftarrow u_i - (x_i - x_j)$ 
9     Update state of robot  $r_i$  using control input  $u_i$ 
10 Return final states of all robots
11 End

```

7.3 Adoption Readiness Evaluation

The ARI metric incorporates all parameters and is optimal for assessing the trade-offs. For all simulation results, the ACR orientation always gives the best results for the ARI metric and shows that the adoption of the proposed approach is encouraging in realistic situations. The sensitivity analysis indicates that the latency weight w_2 dominates a real-time system, the cost weight w_4 dominates a large-scale deployment, and the reliability weight w_1 dominates a safety-critical application.

8 Discussion: Mathematical, Computational, and Practical Implications

The framework proposed in this work provides a rigorous mathematical foundation to characterize the impact of adopting AI-Driven Cloud Robotics (ACR) on the performance, latency, energy consumption, reliability and cost of robotic applications. It is shown that the ACR adoption can be formulated as a constrained optimization problem, where an Adoption Readiness Index (ARI) is introduced to provide explicit quantification of the trade-offs between the aforementioned key design factors [?]. From a mathematical viewpoint, the formulation of ARI leads to the transformation of the adoption into a multi-criteria decision problem with some predefined constraints. Latency requirements lead to non-linear and even discontinuous constraints. Such constraints, however, are generally not related to the specific structure of the problem at hand and therefore may not be efficient [?]. Different from heuristic or rule-based methods, the optimization formulation allows the decision maker to systematically explore the region of solutions representing admissible configurations according to a set of operational constraints. This is essential to avoid overly conservative models or infeasible design choices that could result in instabilities or excessive delays in

real-time and safety-critical robotic applications [?]. The contribution offers even a more general framework using the mathematical concept of graph Laplacian to explicitly model the communication topology and the distributed control.

9 Comparison with Existing Literature

1. Unified modeling: the prior study mainly pays their attention either to computation offloading or to control stability. The proposed architecture extends the modeling, optimization, and analysis results into an abstract, unified modeling framework based on graph theory, enabling to achieve optimal offloading decisions while ensuring the control stability.
2. Adoption-centric perspective: existing studies focus on analyzing the system performance after implementation, while the proposed architecture aims to address the open issue of how to access such system entities for the benefits of pre-deployment end-user adoption decisions considering system performance in terms of control stability and operation cost.
3. Mathematical transparency: the presented unified model employs transparent mathematical formulations to offer insights into the implications underlying the design and the role of various parameters on the quality of the offloading solution.
4. Scalability and generality: the proposed model is not dependent on some specific type of robot, nor on the application domain, and can be adapted to different robotics or CPSs application areas such as advanced manufacturing, and logistics, as well as hospital and health systems robotics.

9.1 Practical Implications for System Designers

The framework offers several guidelines for system designers and engineers:

- Latency-critical tasks can be mathematically constrained to remain at the edge.
- Energy-intensive tasks can be offloaded in order to reduce onboard energy consumption.
- Safety-critical applications can be given higher reliability by weighting coefficients.
- Cost-sensitive deployments can trade cloud usage for better performance.

This can be accomplished by changing the weighting parameters and constraints.

9.2 Limitations and Future Research Directions

Although the proposed framework is general in the sense that many systems can be abstracted or adapted to fit its

structure, there are several limitations to the work. They include the following.

1. Parameter Estimation: The assumed parameterization of latency, energy, and success probabilities may be such that their estimation prior to deployment could be unrealistically accurate.
2. Static Weighting Coefficients: The weighting coefficients w_1 , w_3 , and w_4 are considered static. This may not correctly represent evolving operational priorities.
3. Simplified Network Model: Random access over the network with bounded latency and reliability may not reflect extreme network failures or adversarial conditions.
4. Simulation-Based Validation: The simulation study is extensive and theoretically grounded but does not provide the type of real-world experimental validation that our results could be applied to guide the deployment of a sensor network.

9.3 Directions for Future Research

This work suggests several research avenues:

1. Stochastic and Robust Optimization: While we focus largely on optimization of expected utility, one can model the uncertainty in the environment using a stochastic or even a robust optimization framework. Such a model will be exceedingly helpful in more realistic, dynamic, and uncertain environments.
2. Adaptive Weight Learning: The various utility terms and weighting coefficients in the utility aggregation are heuristically assumed in this work based on expert knowledge. However, learning techniques from artificial intelligence can potentially be used to adaptively learn/utilize the optimum weight factors to compute expected utility based on the observed system performance.
3. Formal Stability Proofs under Delay: Time-delays in the cloud systems often pose significant challenges to the system stability. We would like to study the impact of cloud service delay/latency on time varying utility of robot offloading, using time delay systems theory to derive stronger stability guarantees.
4. Experimental Validation: It is crucial that we test these predictions in the real world, to that end we have already started work on implementing this framework on physical robotic platforms at the MAX/MIN labs. Initial results are not only promising, but demonstrate the utility of the analytic model in predicting robot worlds [?].
5. Policy-Aware Constraints: Finally, while this work captures robot physical and operational limitations; a far richer model would be one that captures regulatory and data-governance constraints which have received surprisingly little attention in the AMS literature to

date. These extensions would further strengthen the applicability of the framework in real-world deployments.

10 Conclusion

The paper provided a complete mathematical and computational framework for the adoption of AI-Driven Cloud Robotics systems; formulated adoption as a constrained optimization problem defined over a Task dependency graph, respecting the system's control structure, and solved by a federated learning algorithm; and introduced an Adoption Readiness Index to quantitatively compare the performance of standalone, edge-only, and cloud-enabled robotic systems under realistic network, computational, and communication constraints. The paper demonstrated the improvements that can be obtained by adopting AI-Driven Cloud Robotics but also the possible degradation that may occur without an appropriate selection of the adoption parameters. The type of contribution that this paper provides is threefold. From a perspective of applied mathematics, we propose a new modulization methodology for which we derive a new result in optimization theory and propose a new solution based on federated learning. From a more practical perspective, we provide to decision-makers a precise, transparent, and easily adaptable tool for steering cloud robotics adoption decisions.

References

- [1] B. Kehoe, S. Patil, P. Abbeel, and K. Goldberg, "A survey of research on cloud robotics and automation," *IEEE Trans. Autom. Sci. Eng.*, vol. 12, no. 2, pp. 398–409, Apr. 2015, doi: 10.1109/TASE.2014.2376492.
- [2] A. K. Tanwani, N. Mor, J. Kubiawicz, and J. E. Gonzalez, "A fog robotics approach to deep robot learning: Application to object recognition and grasp planning," *IEEE Robot. Autom. Lett.*, vol. 4, no. 3, pp. 3059–3066, Jul. 2019, doi: 10.1109/LRA.2019.2922823.
- [3] M. Afrin, J. Jin, A. Rahman, M. Rahman, and S. Kulkarni, "Resource allocation and service provisioning in multi-agent cloud robotics: A comprehensive survey," *ACM Comput. Surv.*, vol. 54, no. 6, pp. 1–36, Aug. 2021, doi: 10.1145/3459996.
- [4] E. Tosello, "Cognitive task planning for smart industrial robots," *Robot. Comput.-Integr. Manuf.*, vol. 42, pp. 12–23, Dec. 2016, doi: 10.1016/j.rcim.2016.03.002.
- [5] M. Chen, Y. Hao, Y. Li, C.-F. Lai, and D. Wu, "On the computation offloading at the edge of mobile cloud computing," *IEEE Netw.*, vol. 33, no. 4, pp. 148–155, Jul./Aug. 2019, doi: 10.1109/MNET.2019.1800231.
- [6] W. Shi, J. Cao, Q. Zhang, Y. Li, and L. Xu, "Edge computing: Vision and challenges," *IEEE Internet Things J.*, vol. 3, no. 5, pp. 637–646, Oct. 2016, doi: 10.1109/JIOT.2016.2579198.

- [7] Y. Mao, J. Zhang, and K. B. Letaief, "Dynamic computation offloading for mobile-edge computing with energy harvesting devices," *IEEE Trans. Wireless Commun.*, vol. 16, no. 4, pp. 2481–2495, Apr. 2017, doi: 10.1109/TWC.2017.2669228.
- [8] Y. Li, M. Chen, W. Dai, and M. Qiu, "Energy-efficient task offloading in cloud robotics systems," *J. Netw. Comput. Appl.*, vol. 178, Art. no. 102970, Apr. 2021, doi: 10.1016/j.jnca.2020.102970.
- [9] K. Zhang, Y. Mao, S. Leng, Y. He, and Y. Zhang, "Energy-efficient offloading for mobile edge computing in 5G heterogeneous networks," *IEEE Trans. Ind. Informat.*, vol. 14, no. 5, pp. 2215–2226, May 2018, doi: 10.1109/TII.2017.2771522.
- [10] J. Goldsmith, G. Veiga, and H. Kress-Gazit, "Cloud-based robotic systems: Challenges and opportunities," *IEEE Access*, vol. 6, pp. 68078–68089, 2018, doi: 10.1109/ACCESS.2018.2879757.
- [11] R. Olfati-Saber, J. A. Fax, and R. M. Murray, "Consensus and cooperation in networked multi-agent systems," *Proc. IEEE*, vol. 95, no. 1, pp. 215–233, Jan. 2007, doi: 10.1109/JPROC.2006.887293.
- [12] W. Ren and R. W. Beard, *Distributed Consensus in Multi-Vehicle Cooperative Control*. London, U.K.: Springer, 2008, doi: 10.1007/978-1-84800-015-5.
- [13] M. Mesbahi and M. Egerstedt, *Graph Theoretic Methods in Multiagent Networks*. Princeton, NJ, USA: Princeton Univ. Press, 2010.
- [14] J.-J. E. Slotine and W. Li, *Applied Nonlinear Control*. Englewood Cliffs, NJ, USA: Prentice Hall, 1991.
- [15] S. Boyd and L. Vandenberghe, *Convex Optimization*. Cambridge, U.K.: Cambridge Univ. Press, 2004.
- [16] D. P. Bertsekas, *Nonlinear Programming*, 3rd ed. Belmont, MA, USA: Athena Scientific, 2016.
- [17] R. T. Rockafellar and R. J.-B. Wets, *Variational Analysis*. Berlin, Germany: Springer, 1998.
- [18] J. Konečný, H. B. McMahan, F. X. Yu, P. Richtárik, A. T. Suresh, and D. Bacon, "Federated learning: Strategies for improving communication efficiency," *arXiv preprint arXiv:1610.05492*, 2016.
- [19] H. B. McMahan, E. Moore, D. Ramage, S. Hampson, and B. A. y Arcas, "Communication-efficient learning of deep networks from decentralized data," in *Proc. 20th Int. Conf. Artif. Intell. Stat. (AISTATS)*, Fort Lauderdale, FL, USA, 2017, pp. 1273–1282.
- [20] M. Alam, I. Awan, and M. Younas, "Trust-aware cloud robotics systems: A probabilistic modeling approach," *IEEE Trans. Cloud Comput.*, vol. 8, no. 4, pp. 1132–1145, Oct.–Dec. 2020, doi: 10.1109/TCC.2017.2769048.
- [21] H. T. Dinh, C. Lee, D. Niyato, and P. Wang, "A survey of mobile cloud computing: Architecture, applications, and approaches," *Wireless Commun. Mobile Comput.*, vol. 13, no. 18, pp. 1587–1611, Dec. 2013, doi: 10.1002/wcm.1203.
- [22] J. Gubbi, R. Buyya, S. Marusic, and M. Palaniswami, "Internet of Things (IoT): A vision, architectural elements, and future directions," *Future Gener. Comput. Syst.*, vol. 29, no. 7, pp. 1645–1660, Sep. 2013, doi: 10.1016/j.future.2013.01.010.
- [23] E. A. Shaban, S. S. Badrakhhan, Y. Aldaaja, N. S. Hamdoon, J. Taha, G. Samara, and M. Odeh, "Mathematical analysis of managerial influences on mobile cloud computing," *Appl. Math. Inf. Sci.*, vol. 19, no. 4, pp. 965–972, Jul. 2025, doi: 10.18576/amis/190420.
- [24] O. Vermesan and P. Friess, *Internet of Things – From Research and Innovation to Market Deployment*. Gistrup, Denmark: River Publishers, 2014.
- [25] J. Lee, B. Bagheri, and H. A. Kao, "A cyber-physical systems architecture for Industry 4.0-based manufacturing systems," *Manufacturing Letters*, vol. 3, pp. 18–23, 2015, doi: 10.1016/j.mfglet.2014.12.001.
- [26] M. M. Odeh, "A proposed theoretical solution for transferring from physical to virtual machines based on cloud computing," in *Proc. 5th Int. Conf. Information Management (ICIM)*, Mar. 2019, pp. 221–226.
- [27] G. Samara, R. Alazaidah, I. Obeidat, M. Alluwaici, and E. Aldaoud, "Strategic Optimization of Convergence and Energy in Federated Learning Systems," *International Arab Journal of Information Technology*, vol. 22, no. 6, pp. 1046–1053, 2025.



Khaled Omar Al-Sheyyab is an Assistant Professor in the Allied Sciences Department at the Faculty of Arts and Sciences, Al-Ahliyya Amman University, Jordan. His research interests include social issues, criminal behavior, cybercrime, human rights, and contemporary societal challenges. He has published several academic studies addressing topics such as cybercrime, hate crimes, psychological trauma and criminal behavior, refugees, and social justice.



Hasan Al-Refai is with the Cybersecurity Department, Faculty of Information Technology, American University of Madaba. is with the Cybersecurity Department, Faculty of Information Technology, American University of Madaba.



Mohammed Salem Ahmed Amayreh is with the Department of History, Faculty of Arts, Ajloun National University. is with the Department of History, Faculty of Arts, Ajloun National University. is with the Department of History, Faculty of Arts, Ajloun National University.

National University.



Mehmet Özdemir holds B.Sc. and M.Sc. degrees in Electrical Engineering from METU, Turkey, and a Ph.D. from Syracuse University, USA, along with a Business Management program from the University of Toronto. He gained extensive industry

experience in broadband communications, serving as Vice President of Engineering at CSI, before moving into academia, teaching at the University of Ontario and Istanbul Sehir University, where he chaired the Electrical Engineering Department. Currently, he is a Full Professor and Chair of the Artificial Intelligence Engineering Department at Istanbul Medipol University.



Ghassan Samara is a Full Professor in the Department of Computer Science, Faculty of Information Technology, Zarqa University, Jordan. He received his Ph.D. degree in Computer Networks from Universiti Sains Malaysia (USM). His research interests

include computer networks, Internet of Things (IoT), vehicular ad hoc networks (VANETs), wireless sensor networks, cloud, fog and edge computing, network security, data privacy, cryptography, and intelligent systems. He has published numerous research articles in international journals and conferences.



Sawsan Baderkhan is a Professor at Al-Ahliyya Amman University, Jordan. She received her Bachelor's, Master's, and Ph.D. degrees from the University of Jordan. Her research focuses on educational studies, educational methods, and philosophical aspects of education. She has published several research studies.



Mahmoud Odeh is an Associate Professor at Zarqa University. He completed his higher education and Ph.D. at Reading and Coventry University, UK. He has more than 15 years of experience in both practical and academic fields, with 56 international certificates in servers, computer virtualization, smart machine simulation, and cloud computing. The rapid evolution of cloud computing technology inspires his current research, primarily focusing on the implementation of innovative technology.